

## i-tec USB-C Dual Display Docking Station with Power Delivery 65W + i-tec Universal Charger 77 W

i-tec USB-C Dual Display Docking Station  
with Power Delivery 65W + i-tec  
Universal Charger 77 W



### PRODUCT DESCRIPTION

USB-C office docking station with support for up to 2 external monitors with 4K resolution. The station is compatible with any laptop equipped with a USB-C or Thunderbolt 3 port. 6x USB ports, reliable and quick connection to your business network thanks to an integrated LAN port and support for installation behind a monitor make the docking station an ideal partner for professionals.

And of course, the station is capable of charging your laptop or tablet with up to 65W (charging adapter included). Integrated latest DP 1.4 protocol supports 5K/60 Hz resolution, making the device suitable for even professional graphics designers, data analysts, film editors and, of course, fans of HD video.

The docking station also comes with a [USB-C power adapter](#) with a total power of 77 W (USB-C port: 65 W and 1x USB-A port with a power of 12W) Should you need to connect your monitor via an HDMI port, you can purchase [DP2HDMI4K60HZ](#) (i-tec DisplayPort to HDMI Adapter), to allow HDMI connection with resolution of up to 4K and refresh rate of up to 60 Hz.

Note: macOS does not support Multi Stream Transport (MST) technology. Connecting two monitors to the station on macOS will result in both monitors showing the same image.

- Connect up to two 4K/30 Hz external monitors
- Power delivery: up to 65 W ([power adapter](#) with a total power of 77 W is included)
- Two available DisplayPorts
- 3x USB 3.1, 1x USB-C 3.1 and 2x USB 2.0 for easy connection of your USB devices and peripherals. Gigabit Ethernet RJ-45 provides reliable, robust and high-speed Internet connection supporting 10/100/1000 Mbps speeds
- Combined jack for audio and microphone on the front panel
- Kensington lock protects against theft, particularly in shared offices or public spaces
- On/off switch for maximum energy savings
- The station features VESA support, allowing smart vertical installation behind a VESA compatible monitor
- Supports Windows 10, macOS X, Android, ChromeOS and Linux

## PRODUCT FEATURES

### DOCKING STATION:

- 1x integrated USB-C cable for connecting to a device (100 cm)
- Docking station technology: [USB-C \(MST\)](#)
- Power Delivery: 65 W
- Video ports: 2x DisplayPort
  - Resolution: DP 1.2 HBR2: 1 monitor - up to 4K/30Hz 2 monitors - up to 2x 1080p/60Hz\*
  - DP 1.4 HBR3: 1 monitor - up to 4K/60Hz 2 monitors - up to 2x 1440p/60Hz\* 2 monitors - up to 2x 4K/30Hz\*
- 1x USB-C port Gen. 2 (data only)
- 1x USB-C port gen. 2 + PD (data + power delivery)
- 3x USB 3.0 port
- 2x USB 2.0 port
- 1x Ethernet GLAN RJ-45 port (Realtek RTL8153)
- 1x 3,5 mm Combo Audio port
- LED indication
- ON/OFF switch for the docking station
- Kensington lock support
- VESA support
- OS: Windows 10, macOS, Android, Chrome OS and Linux with the latest updates
- Product dimensions: 113 x 113 x 40 mm

### CHARGER:

- Input voltage AC 100-240 V, 50-60 Hz
- Output power (max.): 77 W
- USB-C output voltage: DC 5 V / 9 V / 12 V / 15 V / 20 V
- USB-C output current: max. 3.25 A
- USB-A output voltage: DC 5V
- USB-A output current: max. 2.4 A
- Protection against: Current overload, overvoltage, short circuit and overheating.
- Operating temperature: 0°C - 40°C

- Package dimensions: 338 x 150 x 55 mm
- Package weight: 828 g

### Hardware requirements:

- Device with a free USB-C or Thunderbolt 3 port

### Requirements for Power Delivery function:

- Device with a free USB-C or Thunderbolt 3 port with support for Power Delivery technology

### Requirements for video output:

- Device with a free with a Thunderbolt 3 port or with a USB-C port with support for DisplayPort Alternate Mode technology In order for the docking station to provide image refresh rates higher than 60 Hz, a monitor with support for the corresponding refresh rate is required

### Operating system:

- Windows 10, macOS\*, Android, Chrome OS and Linux with the latest updates

\* macOS does not support Multi Stream Transport (MST) technology. Connecting two monitors to the station on macOS will result in both monitors showing the same image.

## SPECIFICATION

| Part Number                  | Product Description & EAN   |
|------------------------------|---|
| C31DUALPDOCKPD65W            | i-tec USB-C Dual Display Docking Station with Power Delivery 65W + i-tec Universal Charger 77 W<br>EAN: 8595611703775   |
| C31DUALPDOCKPD65WUS          | i-tec USB-C Dual Display Docking Station with Power Delivery 65W + i-tec Universal Charger 77 W<br>EAN: 8595611703935   |
| <b>Hardware</b>              |   |
| Bus type                     | USB-C, Thunderbolt-3  |
| <b>Ports/Connectors</b>      |   |
| <b>System Requirements</b>   |   |
| Operating system             | Windows 10<br>macOS X<br>Android<br>Linux<br>Chrome OS R51 or later<br>Windows 10 - Automatic installation of OS drivers. Other operating systems - manual driver installation. |
| <b>Other features</b>        |   |
| Colour                       | black   |
| Housing Material             | ABS   |
| Product Dimensions           | 113 x 113 x 40 mm   |
| Product Weight               |   |
| Package Weight               | 828 g   |
| Packaging Dimensions (LxWxH) | 338 x 150 x 55 mm   |
| <b>Support</b>               |   |
| Warranty period              | 2 years   |
| Technical support            | lifetime  |
| <b>Package contents</b>      |   |
| Product                      |   |
| Instruction manual           |   |
| Universal adapter 77 W       |   |

For further information regarding setup or for answers to FAQ's, please visit our website [i-tec.pro](https://www.i-tec.pro). Specifications are subject to change without notice.

Updated 20.5.2021