

i-tec USB-C Dual HDMI Docking Station with Power Delivery 100 W



PRODUCT DESCRIPTION

Modern USB-C office docking station with support for up to 2 external monitors with 4K resolution. The station is compatible with any laptop equipped with a USB-C, USB4 or Thunderbolt port. 6x USB ports, reliable and quick connection to your business network thanks to an integrated LAN port and support for installation behind a monitor make the docking station an ideal partner for professionals. And of course, the station is capable of charging your laptop or tablet with up to 100W.

- Connect up to two 4K/60 Hz external monitors
- Power delivery: up to 100 W
- Two available HDMI ports
- 6x USB ports: 1x USB-C (10Gbps), 1x USB-C (5Gbps), 2x USB-A (5Gbps) and 2x USB-A 2.0 for easy connection of your USB devices and peripherals.
- Gigabit Ethernet RJ-45 provides reliable, robust and high-speed Internet connection supporting 10/100/1000 Mbps speeds
- Combined jack for audio and microphone on the front panel
- Kensington lock protects against theft, particularly in shared offices or public spaces
- On/off switch for maximum energy savings
- The station features VESA support, allowing smart vertical installation behind a VESA compatible monitor
- Supports Windows 10/11, macOS*, Android, iPadOS, ChromeOS and Linux

The docking station is available in two versions:

1. **without enclosed USB-C charging adapter (product code [C31DUALHDMIDOCKPD](#) - this version).**
2. **with enclosed 100W adapter (product code [C31DUALHDMIDPD100/UK](#))**

*macOS does not support Multi Stream Transport (MST) technology. Connecting two monitors to the station on macOS will result in both monitors showing the same image.

The docking station can be used without the power adapter. In that case, the station's HDMI, LAN (RJ-45) port, audio/mic and both USB 2.0 ports will always be operational. However, the USB-A 3.2 Gen 1 ports and the USB-C data port may not function if a device with higher power requirements is connected (e.g. SSDs, particularly NVMe units). In that case, the docking station may switch off. To use all ports and achieve maximum data transmission speed, it is recommended to use the docking station with the power adapter plugged in.

NOTE: USB-C charger is not included. If you require a docking station with an included USB-C charger, consider the version with product number [C31DUALHDMIDPD100](#).

PRODUCT FEATURES

- 1x integrated USB-C cable for connecting to a host device (100 cm)
- Docking station technology: [USB-C \(MST\)](#) + [USB-C PD](#)
- Power Delivery: up to 100W
- Video Ports: 2x HDMI 2.0
- **Resolutions:**
- **Host device with DisplayPort 1.2 support:**
 - 1 monitor:
 - 1x HDMI → up to 4K/30Hz
 - 1x HDMI → up to 1080p/120Hz
 - 2 monitors:
 - 2x HDMI → up to 2x 1080p/60Hz*
- **Host device with DisplayPort 1.4 support:**
 - 1 monitor:
 - 1x HDMI → up to 4K/60Hz
 - 1x HDMI → up to 1440p/144Hz or 1080p/240Hz
 - 2 monitors:
 - 2x HDMI → up to 2x 1440p/60Hz* or 2x 4K/30Hz*

- **Host device with DisplayPort 1.4 with DSC support:**

- 1 monitor:
 - 1x HDMI → up to 4K/60Hz
 - 1x HDMI → up to 1440p/144Hz or 1080p/240Hz
- 2 monitors:
 - 2x HDMI → up to 2x 4K/60Hz* or 1440p/144Hz*

- 1x USB-C 3.2 Gen 2 (10 Gbps)
- 1x USB-C 3.2 Gen 1 (5 Gbps)
- 2x USB-A 3.2 Gen 1 (5 Gbps)
- 2x USB-A 2.0
- 1x USB-C Power Delivery port (up to 20V/5A, max 100W) + USB data Gen 2 (10 Gbps)
- 1x Ethernet RJ-45 1Gbps
- 1x 3.5 Combo Audio port
- MAC Address cloning: Yes (using [i-tec Docker Pro](#) software)
- LED indication
- ON/OFF switch for the docking station
- Kensington lock support
- OS: Windows 10 / 11, macOS*, Android**, iPadOS**, ChromeOS, Linux
- Product dimensions: 113 x 113 x 26 mm
- Product weight: 242 g

Hardware requirements:

- Device with free USB-C, USB4 or Thunderbolt™ 3/4/5

Power Delivery requirements:

- Device with a free USB-C, USB4 or Thunderbolt™ 3/4/5 with Power Delivery support

Video Output requirements:

- Device with a free USB-C or USB4 with “DisplayPort Alternate Mode or Thunderbolt™ 3/4/5 support.

Operating System:

- Windows 10 / 11, macOS*, Android**, iPadOS**, ChromeOS, Linux

* macOS does not support Multi Stream Transport (MST) technology. Connecting two monitors to the station on macOS will result in both monitors showing the same image.

** iPadOS, Android do not support multi-screen video transfer technology, nor the extended screen option. This means that when connected to an external monitor, only the mirrored screen will be displayed. (Not valid for androids with DEX and Easy Projection extension)

The docking station can be used without the power adapter. In that case, the station's HDMI, LAN (RJ-45) port, audio/mic and both USB 2.0 ports will always be operational. However, the USB-A 3.2 Gen 1 ports and the USB-C data port may not function if a device with higher power requirements is connected (e.g. SSDs, particularly NVMe units). In that case, the docking station may switch off. To use all ports and achieve maximum data transmission speed, it is recommended to use the docking station with the power adapter plugged in.

SPECIFICATION

PART NUMBER	PRODUCT DESCRIPTION & EAN
C31DUALHDMIDOCKPD	i-tec USB-C Dual HDMI Docking Station with Power Delivery 100 W EAN: 8595611707377
Hardware	
Bus type	USB-C, Thunderbolt-3, Thunderbolt-4, Thunderbolt-5, USB4
System Requirements	
Operating system	Windows 10/11 macOS X Android Linux Chrome OS R51 or later Windows 10 - Automatic installation of OS drivers. Other operating systems - manual driver installation. Firmware updates automatically.
Other features	
Product Dimensions	113 × 113 × 26 mm
Product Weight	242 g
Support	
Warranty period	2 years
Technical support	Lifetime
Package contents	
<ul style="list-style-type: none">• Product• Manual	



i-tec USB-C Dual HDMI Docking Station with Power Delivery 100 W

For further information regarding setup or for answers to FAQ's, please visit our website [i-tec.pro](https://www.i-tec.pro).
Specifications are subject to change without notice.

Updated 06/02/2026 11:54:18