

## i-tec USB-C/Thunderbolt KVM Docking station Dual Display + Power Delivery 65/100W

i-tec USB-C/Thunderbolt KVM Docking station Dual Display + Power Delivery 65/100W



### PRODUCT DESCRIPTION

A USB-C docking station that lets you connect up to two computers at once. Switching between the connected computers is simple - at the touch of a button. So you can have two computers connected to the docking station (for example, in a meeting room), or perhaps a computer and a tablet (or smartphone) in your workplace.

The KVM dock allows you to work more easily and efficiently, sharing work on multiple computers on external monitors, eliminating the need to constantly switch USB-C cables. Both computers can be powered at the same time\*.

The workstation supports output to up to two external monitors, and any laptop with a Thunderbolt or USB-C port (with video transfer support) can be connected.

\* Connection of an optional power supply (not included) to the docking station's power port is required to power the second computer

Note: The macOS operating system does not support Multi Stream Transport (MST) video transfer technology, which means that if connected to macOS, the same image will be projected on both monitors.

### PRODUCT FEATURES

- 2x USB-C port for connecting to compatible devices
- Power: PC1 port - up to 100W (additional USB-C power adapter is required to power through this port)
- Port PC2 - up to 65W
- Docking Station Technology: USB-C (MST)
- Video ports: 1x DisplayPort, 1x HDMI
- Resolution:
  - USB-C/USB4/Thunderbolt™ 3/4 with DisplayPort 1.4 support without DSC support
    - 1 monitor - 1x DP or 1x HDMI - up to 4K/60Hz
    - 2 monitors - 1x DP + 1x HDMI - up to 2x 2560×1440/60Hz

- USB-C/USB4/Thunderbolt™ 3/4 with DisplayPort 1.2 support
  - 1 monitor - 1x DP or 1x HDMI - up to 4K/30Hz
  - 2 monitors - 1x DP + 1x HDMI - up to 2x 1920x1080/60Hz
- 2x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 with fast charging support (BC 1.2)
- 1x USB-C power only (power pass-through for PC1 port)
- 2x USB-C 3.2 Gen 1
- 1x Ethernet GLAN RJ-45 port (ASIX AX88179)
- 1x 3.5mm audio combo port
- 1x 3.5mm switch port (this port is for connecting a HW switch.)
- 1x power input (20V/6A)
- Power button to turn the docking station on/off and to switch between inputs
- LED indication
- Kensington lock support
- USB-C cable (100 cm)
- OS: Windows 10/11, macOS, Android, iPadOS, Chrome OS and Linux with latest updates
- Product dimensions: 185 x 79 x 28 mm
- Product weight: 265 g
- Package dimensions: 250 x 205 x 50 mm

#### Hardware requirements:

- Device with a free USB-C, USB4 or Thunderbolt™ 3/4 port

#### Power Delivery Requirements:

- Devices with a free USB-C, USB4 or Thunderbolt™ 3/4 port with "Power Delivery" support.

#### Video Output Requirements:

- Devices with a free USB-C, USB4 port with "DisplayPort Alternate Mode" support or Thunderbolt™ 3/4 port

## SPECIFICATION

Part Number	Product Description & EAN
C31DUALKVMDOCKPD	i-tec USB-C/Thunderbolt KVM Docking station Dual Display + Power Delivery 65/100W EAN: 8595611705250
C31DUALKVMDOCKPDUK	i-tec USB-C/Thunderbolt KVM Docking station Dual Display + Power Delivery 65/100W EAN: 8595611705267
<b>Hardware</b>	
Bus type	USB-C, Thunderbolt-3, Thunderbolt-4
<b>Ports/Connectors</b>	
<b>System Requirements</b>	
Operating system	Windows 10 macOS X Android Linux Chrome OS R51 or later Windows 10 - Automatic installation of OS drivers. Other operating systems - manual driver installation. Firmware

	updates automatically.
<b>Other features</b>	
Colour	black
Housing Material	ABS
Product Dimensions	185 x 79 x 28 mm
Product Weight	265 g
Package Weight	
Packaging Dimensions (LxWxH)	250 x 205 x 50 mm
<b>Support</b>	
Warranty period	2 years
Technical support	lifetime
<b>Package contents</b>	
Docking station	
Manual	

For further information regarding setup or for answers to FAQ's, please visit our website [i-tec.pro](https://www.i-tec.pro). Specifications are subject to change without notice.

Updated 16.5.2022