

i-tec USB-C Triple Display Docking Station Gen 2 Pro + Power Delivery 100W



PRODUCT DESCRIPTION

A high-performance, new generation USB-C docking station that supports output to up to three external monitors in up to 4K high resolution. The dock can be used with virtually all notebooks equipped with USB-C, USB4 and Thunderbolt ports, while supporting all common current operating systems.

Plenty of USB ports (including those supporting speeds of up to 10 Gbps), reliable and fast connection to the corporate network thanks to the integrated LAN port and support for installation behind the monitor all make this docking station the ideal companion for true professionals. Of course, it supports charging of your laptop or tablet, up to 100 W.

- Connect to 3 external monitors in resolutions up to 4K*
- Power delivery: up to 100 W
- 2 DisplayPort and 1 HDMI port available
- 6 USB ports: 2x USB-C (10 Gbps and 4x USB-A (1x Gen 2 (10 Gbps) supporting BC 1.2 fast charging and 3x Gen 1 (5 Gbps).
- Gigabit Ethernet RJ-45 provides reliable, robust and high-speed internet connectivity with support for 10/100/1000 Mbps speeds
- Combo jack for audio and microphone
- Kensington lock provides anti-theft protection, especially in shared office environments or public areas
- Docking station power switch allows for maximum power savings
- Docking station supports a VESA mount for smart vertical installation behind a VESA-enabled monitor
- Supports Windows 10 / 11, macOS*, Android**, iPadOS**, ChromeOS, Linux

** macOS does not support Multi Stream Transport (MST). Connecting two or more monitors to a macOS station will cause all monitors to display the same image*

*** iPadOS, Android do not support multi-screen transport technology or the extended screen option. This means that when connected to an external monitor, only the mirrored screen will be displayed. (Not valid for Android devices with DEX and Easy Projection extensions).*

PRODUCT FEATURES

- 1x USB-C port for connection to a laptop (100 cm USB-C cable included)
- Docking station technology: [USB-C \(MST\)](#)
- Power Delivery: 100 W
- Video Ports:
 - 2x DisplayPort
 - 1x HDMI
- **Resolution:**
- **Host device with DisplayPort 1.2 support:**
 - 1 monitor:
 - 1x DP or HDMI → up to 4K/30Hz
 - 1x DP or HDMI → up to 1080p/120Hz
 - 2 monitors:
 - 1x DP + 1x HDMI → up to 2x 1080p/60Hz*.
 - 2x DP → up to 2x 1080p/60Hz*
 - 3 monitors:
 - 1x DP + 1x DP + 1x HDMI → up to 1x 1080p/60Hz + up to 2x 720p/60Hz*
- **Host device with DisplayPort 1.4 support:**
 - 1 monitor:
 - 1x DP or HDMI → up to 4K/60Hz
 - 2 monitors:
 - 1x DP + 1x HDMI → up to 2x 1440p/60Hz*
 - 1x DP + 1x HDMI → up to 2x 4K/30Hz*
 - 2x DP → up to 2x 4K/30Hz*
 - 3 monitors:

- 1x DP + 1x DP + 1x HDMI → up to 3x 1080p/60Hz*

- **Host device with DisplayPort 1.4 with DSC support:**

- 1 monitor:
 - 1x DP or HDMI → up to 4K/60Hz
 - 1x DP → up to 4K/144Hz or 1440p/240Hz or 1080p/360Hz
 - 1x HDMI → up to 1440p/144Hz or 1080p/240Hz
- 2 monitors:
 - 1x DP + 1x HDMI → up to 2x 4K/60Hz*
 - 1x DP + 1x HDMI → up to 2x 1440p/144Hz*
- 3 monitors:
 - 1x DP + 1x DP + 1x HDMI → up to 3x 4K/30Hz*

- 2x USB-C 3.2 Gen 2 (10Gbps, data only)
- 3x USB-A 3.2 Gen 1 (5Gbps)
- 1x USB-A 3.2 Gen 2 (10Gbps) with fast charging support (BC 1.2)
- 1x Ethernet GLAN RJ-45 port (Realtek RTL8153)
- 1x 3.5mm Audio combo jack
- 1x power input (20V/6.5A)
- MAC address cloning: yes (using [i-tec Docker Pro](#) software)
- WOL: S1, S2, S3
- ON/OFF switch to turn the docking station on and off
- LED indication
- Support for Kensington lock
- Support for VESA mounting
- USB-C 3.2 Gen2 cable (100 cm)
- OS: Windows 10 / 11, macOS*, Android**, iPadOS**, ChromeOS, Linux
- Product dimensions: 212 x 82 x 23 mm
- Product weight: 366 g

Hardware requirements:

- Device with a free USB-C, USB4 or Thunderbolt™ 3/4/5 port

Power Delivery Requirements:

- Device with a free USB-C, USB4, or Thunderbolt™ 3/4/5 port with Power Delivery support

Video Output Requirements:

- Device with a free USB-C or USB4 port with DisplayPort Alternate Mode support or Thunderbolt™ 3/4/5 port

Operating System:

- Windows 10 / 11, macOS*, Android**, iPadOS**, ChromeOS, Linux

*macOS does not support Multi Stream Transport (MST) technology. Connecting two monitors to a macOS station will cause both monitors to display the same image.

** iPadOS, Android do not support multi-screen transport technology or the extended screen option. This means that when connected to an external monitor, only the mirrored screen will be displayed. (Not valid for Android devices with DEX and Easy Projection extensions).

SPECIFICATION

PART NUMBER	PRODUCT DESCRIPTION & EAN
C31TRIPLEDOCKPDPRO2	i-tec USB-C Triple Display Docking Station Gen 2 Pro + Power Delivery 100W EAN: 8595611706592
C31TRIPLEDOCKPDPRO2UK	i-tec USB-C Triple Display Docking Station Gen 2 Pro + Power Delivery 100W EAN: 8595611706790
Hardware	
Bus type	USB-C, Thunderbolt-3, Thunderbolt-4, USB4
System Requirements	
Operating system	Windows 10/11 macOS X Android Linux Chrome OS R51 or later Windows 10 - Automatic installation of OS drivers. Other operating systems - manual driver installation. Firmware updates automatically.
Other features	
Product Dimensions	212 x 82 x 23 mm



i-tec USB-C Triple Display Docking Station Gen 2 Pro + Power Delivery 100W

Product Weight 366 g

Support

Warranty period 2 years

Technical support Lifetime

Package contents

- Product
- USB cable from type C to type C (100cm)
- Power adapter
- Manual

For further information regarding setup or for answers to FAQ's, please visit our website [i-tec.pro](https://www.i-tec.pro). Specifications are subject to change without notice.

Updated 05/02/2026 09:36:48