i-tec Thunderbolt 3 Travel Dock Dual 4K Display + Power Delivery 60W

i-tec Thunderbolt 3 Travel Dock Dual 4K
Display + Power Delivery 60W

PRODUCT DESCRIPTION

For functionality with Macbook Air M1, you must use a USB-C power adapter (not included) with at least 45W of power.   Docking station combining compact size with extreme performance supported by Thunderbolt" 3 technology. Though the station is designed primarily for use on your travels due to its size and weight, its performance is not limited by any compromises! Video resolution of up to 8K, or 2x 4K, on both Windows 10 and macOS.

It is also the first docking station built on Thunderbolt" 3 technology and designed primarily for travelling professionals. The station supports laptop charging via a USB-C (TB3) port with up to 60 W*. This will allow you to charge any laptop, even those that require a charging output of 100 W (e.g. a MacBook Pro 16"), though the charging may take a little longer.   Naturally, the station also features an integrated LAN port, USB ports (one of which offers bitrates of up to 10 Gbps) and support for audio output and microphone.

- Connect up to two 4K external monitors or one monitor in 8K/30 Hz resolution
- Power delivery: up to 60 W (power adapter not included)
- DisplayPort and HDMI port available
- 1x USB 3.1 Gen 2 (10 Gbps) and 1x USB 2.0 will allow you to easily connect your USB devices and peripherals
- Gigabit Ethernet RJ-45 provides reliable, robust and high-speed Internet connection supporting 10/100/1000 Mbps speeds
- Combined jack for audio and microphone
- Supports Windows 10, macOS X
- Note: Power supply not included. The dock can be used with the PSU supplied with the laptop, or a power supply can be purchased separately, P/N CHARGER-C112W/UK.

 * The docking station must be used in combination with your USB-C power adapter (not included) in order to function properly.

PRODUCT FEATURES

- 1x integrated Thunderbolt™ 3 cable for connecting to a device (18 cm)
- Docking station technology: Thunderbolt™ 3
- Power Delivery: 60W
    - Internal power consumption: 15W (more info here)
- Video ports:
    - 1x Display Port
    - 1x HDMI
- Resolution:
- **Thunderbolt™ 3/4 Host device with DisplayPort 1.4 support:**
    - 1 monitor – 1x DP → up to 8K/30Hz*
    - 1 monitor – 1x DP – up to 4K/144Hz or 1440p/240Hz or 1080p/360Hz
    - 1 monitor – 1x HDMI → up to 4K/60Hz
    - 1 monitor – 1x HDMI → up to 1440p/144Hz
    - 2 monitors – 1x HDMI + 1x DP → up to 2x 4K/60Hz or 2x 1440p/144Hz or 2x 1080p/240Hz
- **Thunderbolt™ 3 Host device with DisplayPort 1.2 support:**
    - 1 monitor – 1x DP → up to 5K/60Hz
    - 1 monitor – 1x DP → up to 1440p/240Hz or 1080p/360Hz
    - 1 monitor – 1x HDMI → up to 4K/60Hz
    - 1 monitor – 1x HDMI → up to 1440p/144Hz
    - 2 monitors – 1x HDMI + 1x DP → up to 2x 4K/60Hz or 2x 1440p/144Hz or 2x 1080p/240Hz
- 1x USB-C PD port (power delivery only)
- 1x USB 3.1 Gen 2 port (10 Gbps)
- 1x USB 2.0 port
- 1x Ethernet GLAN RJ-45 port (Realtek RTL8153)
- 1x 3.5 mm combo audio jack
- MAC Address cloning: Yes (using i-tec Docker Pro software)
- WOL: S1, S2, S3
- Integrated USB-C cable (18 cm)
- OS: Windows 10 / 11, macOS and Linux with latest updates
- Product dimensions: 100 x 100 x 28 mm
- Product weight: 210 g
- Package dimensions: 133 x 165 x 38 mm
- Package weight: 300 g

Hardware Requirements:

- Device with a free Thunderbolt™ 3/4 port

Power Delivery Requirements:

- Device with a free Thunderbolt™ 3/4 port with Power Delivery support

Video Output Requirements:

- Device with a free Thunderbolt™ 3/4 port

Operating System:

- Windows 10 / 11, macOS and Linux with latest updates

* 8K resolution must be supported by the connected laptop or tablet.

SPECIFICATION

Part Number	Product Description & EAN

TB3TRAVELDOCKPD	i-tec Thunderbolt 3 Travel Dock Dual 4K Display + Power Delivery 60W EAN: 8595611703744
Hardware	
Bus type	Thunderbolt-3, Thunderbolt-4
Ports/Connectors	
System Requirements	
Operating system	Windows 10/11 macOS X Linux
Other features	
Colour	black
Housing Material	ABS
Product Dimensions	100 x 100 x 28 mm
Product Weight	210 g
Package Weight	300 g
Packaging Dimensions (LxWxH)	133 x 165 x 38 mm
Support	
Warranty period	2 years
Technical support	lifetime
Package contents	
Product	
Instruction manual	

For further information regarding setup or for answers to FAQ's, please visit our website i-tec.pro.
Specifications are subject to change without notice.

Updated 13.4.2023